


TCXO (Temperature Compensated Crystal Oscillator)

Size: 2.0×1.6×0.75 mm

7X Series SMD 2016 TCXO /VC-TCXO

Features


- Output frequency: 10~52MHz
- 2016 size, 0.75mm high SMD TCXO/VCTCXO
- Low voltage operation and low phase noise
- Temperature stability: $\pm 0.5\text{ppm} \sim \pm 2.0\text{ppm}$
- VCTCXO available
- Automatic mounting and reflow soldering
- Applications: Phone, GPS, WiMAX, WLAN, IoT, Wearable electronics, etc.
- RoHS Compliant /Pb Free



Standard Specification

Item /Type		7X (SMD 2016 TCXO /VC-TCXO)
Output Type		Clipped Sinewave
Output Load		10K Ω //10pF
Supply Voltage		1.8~3.3V
Frequency Range		10~52 MHz
Supply Current		2.0mA Max.
Output Level		0.8 Vp-p Min.
Frequency Stability	Tolerance	$\pm 2.0\text{ppm}$ Max. (after 2 reflows)
	vs Temperature	$\pm 0.5\text{ppm} \sim \pm 2.5\text{ppm}$. /-30~+85°C
	vs Supply Voltage	$\pm 0.2\text{ppm}$ Max. (Vcc $\pm 5\%$)
	vs Load	$\pm 0.2\text{ppm}$ Max. (Load varies $\pm 10\%$)
	vs Aging	$\pm 1.0\text{ppm}$ Max. /Year
Auto Frequency Control (AFC) Range*		$\pm 7 \sim \pm 16\text{ppm}$ (1.4 $\pm 1\text{V}$)
Start-up Time		2ms Max.
Operating Temperature		-30~+85°C
Phase Noise @19.2MHz	100Hz	-115dBc/Hz
	1KHz	-135dBc/Hz
	10KHz	-148dBc/Hz
Packing Unit		3000pcs./Reel

Dimensions [mm]



Pin Connections

Pin No.	Connection
1	Vcon(VC-TCXO)/GND(TCXO) Enable /Disable (Stand-by function)
2	GND
3	Output
4	Vcc

